



COLIBRI' UFO75 , the new product created for finishing semi-dry or concrete floor surfaces. Specially designed for leveling and smoothing concrete surfaces such as industrial floors, garages, cellars, vaults, corridors and any other surface with reduced operating space or finish with quartz.

COLIBRI' UFO75 'thanks to its lightness and to the handlebar extensible can also be driven with only one hand. It does not transmit vibrations damaged to the operator and can be conducted at your fingertips without the slightest fatigue. is equipped with a knob wheel which adjusts the height of the handle. This device allows you to use the handle with different lengths by using the not standard extensions available as spares.

TECHNICAL SPECIFICATIONS

	Width	Unit of measure
Machine body weight	30	kg
Maximum overall	0,75 x 3.80 X 0,5	m
Minimum overall	0,75 x 1,65 x 0,5	m
Fuel tank capacity	0,65 - 650	l - cm ³
Piston displacement	33.5	cm ³
Maximum power (according to ISO 8893)	1,18	kW
Engine rating speed	5000	min ⁻¹
Engine speed to the max power	8000	min ⁻¹
Specific consumption engine to the max power (according to ISO 8893)	340	g/kW*h
Acoustic pressure level (L _{pa av})	84	dBA
Acoustic power level (L _{Wa av})	100	dBA
Vibration level	< 2,5	m/s ²
Disk rotation speed	30-80	min ⁻¹

Description and illustrations are only indicative; the products may present different characteristics for construction purposes. D'Alessandro Group reserves the right to modify any of its products